

Q8 Formula Advanced

10W-40

Description

Advanced Performance Synthetic Based Engine Oil

Application

High quality synthetic based engine oil formulated with Q8 hydro-cracked components.

Recommended for passenger cars and vans equipped with modern gasoline or LPG engines with catalysts.

Also suitable for normally aspirated or turbocharged diesel engines with or without direct injection.

Specifications

- ACEA A3
- ACEA B3
- ACEA B4
- API SL/CF
- MB-Approval 229.1
- VW 505.00

Benefits

- Synthetic based year round engine lubricant
- Good engine protection after cold starting
- Reduces engine fuel consumption
- Retains high viscosity index providing strong lubricant film at different operating conditions
- Good engine performance under different driving circumstances
- Good protection against rust and corrosion
- Prevents formation of black sludge

Specifications

Specification	Method	Units	
Viscosity Grade	-	-	SAE 10W-40
Absolute Density, 15 °C	D 4052	kg/m ³	874
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.5
Kinematic Viscosity, 40 °C	D 445	mm ² /s	98.5
Viscosity Index	D 2270	-	152
Apparent Viscosity, -25 °C	IP 383	mPa.s	6600
Borderline Pumping Temperature	D 3829	°C	-30.2
Pour Point	D 97	°C	-30
Flash Point	D 93	°C	202
Viscosity at high temp. & high shear rate	CEC-L-36-A-90	mPa.s	>=3.5

To be able to offer our clients products with constantly better characteristics, Kuwait Petroleum reserves the right, without further notice, to modify the specifications of its products at all times.

KUWAIT PETROLEUM INTERNATIONAL LUBRICANTS - NORTHWEST EUROPE

Belgium: Technische dienst
+32 (0) 3 241 37 93
www.Q8oils.be

Luxemburg: Service Technique
+32 (0) 3 241 37 93
www.Q8oils.lu

The Netherlands: Technische dienst
+31 (0) 10 407 21 07
www.Q8oils.nl

KPBNL-Q08